

KEJIA TRADE

PRODUCT CATALOG

UV PRINTING SYSTEMS

Flatbed, roll-to-roll, floor and wall printers

- Flatbed
- Roll-to-roll
- Floor
- Wall

Models, specifications and configurations

11600		(Epson 11600
A2+	(A2+special-shaped product printer)	(mode
		(print
		(print s
		(Print h
		X (X-axis
		Y (Y-axis
		(Ink consu
		(Ink suppl
		(Use i
		(curing m
		uv (uv light
		(Platform re
		(size of c
(Number of sprinkler heads):		2 (two)
		(packag

A3 uv (a3 upgraded uv printer)

$$(\text{mod } l)$$

A3 3040UV



(Print nozzle): (Original imported ultra HD print head.)

(Color software): / / (Meng tai Rui Cai Rui yin)

/ (Net weight, gross weight): 60KG/100KG(about60kg/100kg)

(outer packing): (Fumigated export wooden cases)

```
(print size):
```

30*40CM

```
(print speed) :
```

(Adjustable high and low medium speed)

(Print height) :

0-15CM

X

(X-axis drive) :

(Adopt silent guide rail, no noise)

(Ink consumption) :

/1.5 (One square 1.5ml)

(Ink supply mode) :

6-8

() (Six to eight color white ink circulation stirring to prevent precipitation)

(Use ink) :

UV

、 、 (Uv ink Textile ink uses ink)

(curing method) :

/ UV (Water-cooled air-cooled UV lamp)

UV

(uv light power) :

90W

(Platform regulation):

+ / (Automatic adjustment plus touch screen)

(size of device):

660*600*520mm

(package size) :

990*890*790mm

(outer packing) :

(Fumigated export wooden cases)

(Power requirement) :

AC220/110+1050~60HzP00W

(ink supply system) :

/ + (The software automatically feeds ink
Spray and automatic cleaning)

(OS):

Windows

(Cylinder function):

(:) (Support printing cylinder function
another option)

A3+ uv (a3+ upgraded uv printer)

$$(\text{mod } l)$$

A3+3360UV



(Print nozzle): (Original imported ultra HD print head.)

(Color software): / / (Meng tai Rui Cai
Rui yin)

/ (Net weight, gross weight): 70KG/110KG(about60kg/100kg)

(outer packing): (Fumigated export wooden cases)

```
(print size) :
```

33*60CM

```
(print speed) :
```

(Adjustable high and low medium speed)

(Print height) :

0-18CM

X

(X-axis drive) :

(Adopt silent guide rail, no noise)

(lnk consumption) :

/1.5 (One square 1.5ml)

(Ink supply mode) :

6-8

() (Six to eight color white ink circulation stirring to prevent precipitation)

(Use ink) :

UV

(Uv ink Textile ink uses ink)

(curing method) :

/ UV (Water-cooled air-cooled UV lamp)

UV

(uv light power) :

90W

(Platform regulation):

+ / (Automatic adjustment plus touch screen)

(size of device) :

860*800*610mm

(package size) :

990*890*790mm

(outer packing) :

(Fumigated export wooden cases)

(Power requirement) :

AC220/110+1050~60HzP00W

(ink supply system) :

/ + (The software automatically feeds ink
Spray and automatic cleaning)

(OS) :

Windows

(Cylinder function):

(:) (Support printing cylinder function
another option)

4060uv (A2+upgraded uv printer)



(modle)

:

4060UV (4060 uv printer)

(print size):

60*40CM

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-15CM

X (X-axis drive):

(Adopt silent guide rail, no noise)

Y (Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

6-8

(

)

(Six to eight color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

、

、

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv (uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

76*950*600mm

(package size):

1100 950 830 mm

(Number of sprinkler heads):

2

(two)

(Platform material):

/

(Steel

adsorption platform)

(outer packing):

(Fumigated export wooden cases)

(Printing direction) :

/

(Single item

bidirectional printing.)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported ultra-light
print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic cleaning)

(Color software):

/

/

(Meng tai

Rui Cai Rui yin)

(OS):

Windows

/ (Net weight, gross weight):

80KG/130KG(About 80or
130kg)

(Cylinder function):

(

:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated
export wooden cases)() (Printing color
(colour)) :

+

(Bai Cai Jia guang you)

(layout):

TIF、PDF、TIF、jpg、CAD、CDR、

4060
upgraded roll flat integrated printer.)

uv (A2 +

(modle)

:

4060

(4060Roll-flat integrated printer)

(print size):

60*40CM

(Crystal scale size):

30CM *100 (30cm wide and 100m long)

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-15CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

6

(

)(Six color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

,

,

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

840*980*680mm

(package size):

1100 950 830 mm

(Number of
sprinkler heads):

2

(two)

(Platform
material):

(Adsorption
platform)

(outer packing):

(Fumigated export wooden cases)

(Printing
direction) :

/

(Single item
bidirectional printing)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported ultra-light
print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic
cleaning)

(Color software):

/ / (Meng tai
Rui Cai Rui yin)

(OS):

Windows

/ (Net weight,
gross weight):

100KG/140KG

(Cylinder function):

(:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated
export wooden cases)

(Printing colo) :

+

(White color +gloss oil)





A2+ uv (A2+upgraded uv printer)

(modle)

:

A2+6050UV

(A2+6050 uv printer)

(print size):

60*50CM

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-23CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

6-8

(

)(Six to eight color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

、

、

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

990*900*640mm

(package size):

1100 950 830 mm

(Number of sprinkler heads):

2

(two)

(Platform material):

/

(Steel

adsorption platform)

(outer packing):

(Fumigated export wooden cases)

(Printing direction) :

/

(Single item

bidirectional printing.)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported ultra-light
print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic cleaning)

(Color software):

/

/

(Meng tai

Rui Cai Rui yin)

(OS):

Windows

/

(Net weight, gross weight):

80KG/130KG(About 80or
130kg)

(Cylinder function):

(

:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated
export wooden cases)() (Printing color
(colour)) :

+

(Bai Cai Jia guang you)

(layout):

TIF、PDF、TIF、jpg、CAD、CDR、

A2+
upgraded roll flat integrated printer.)

uv (A2+

(modle)
:

A2+

(A2+Roll-flat integrated printer)

(print size):

60*50CM

(Crystal scale size):

30CM *100 (30cm wide and 100m long)

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-23CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

6

(

)(Six color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

,

,

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

840*980*680mm

(package size):

1100 950 830 mm

(Number of
sprinkler heads):

2

(two)

(Platform
material):

(Adsorption
platform)

(outer packing):

(Fumigated export wooden cases)

(Printing
direction) :

/

(Single item
bidirectional printing)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported ultra-light
print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic
cleaning)

(Color software):

/ / (Meng tai
Rui Cai Rui yin)

(OS):

Windows

/ (Net weight,
gross weight):

100KG/140KG

(Cylinder function):

(:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated
export wooden cases)

(Printing colo) :

+

(White color +gloss oil)



6060	uv	(6060 upgraded uv printer)	(modle) :	6060-UV	(6060-uv printer)
			(print size):	60*60CM	
			(print speed):	5-10 /	(5~10 square hours)
			(Print height):	0-23CM	
			X (X-axis drive):	(Adopt silent guide rail, no noise)	
			Y (Y-axis drive):	Y	(Y-axis double guide screw drive improves printing accuracy)
			(Ink consumption):	/1.5	(One square 1.5ml)
			(Ink supply mode):	6-8	(Six to eight color white ink circulation stirring to prevent precipitation)
			(Use ink):	UV 、	(Uv ink Textile ink uses ink)
			(curing method):	/ UV	(Water-cooled air-cooled UV lamp)
			uv (uv light power):	120W	
			(Platform regulation):	+ /	(Automatic adjustment plus touch screen)
			(size of device):	1370*1200*700mm	
			(package size):	1500*1350*880mm	
(Number of sprinkler heads):	3	(three)	(outer packing):	(Fumigated export wooden cases)	
(Platform material):	(Adsorption platform)		(Power requirement):	AC220/110+1050~60HzP00W	
(Printing direction) :	/	(Single item bidirectional printing)	(ink supply system):	/ +	(The software automatically feeds ink Spray and automatic cleaning)
(Print nozzle) :	(Imported ultra-light print head)		(OS):	Windows	
(Color software):	/ /	(Meng tai Rui Cai Rui yin)	(Cylinder function):	(:) (Support printing cylinder function another option)	
/ (Net weight, gross weight):	200KG/220KG		(Printing color (colour)) :	() + + (White+ gloss+ oil)	
(outer packing):	(Fumigated export wooden cases)				



6060 uv printer with integrated screen rolling.)	(6060 upgraded uv printer with integrated screen rolling.)	(modle) :	6060	(6060 roll-flat integrated printer)
		(print size):		60*60CM
		(Crystal scale size):	30CM *100	(30cm wide and 100m long)
		(print speed):		(Adjustable high and low medium speed)
		(Print height):		0-23CM
		X (X-axis drive):		(Adopt silent guide rail, no noise)
		Y (Y-axis drive):	Y	(Y-axis double guide screw drive improves printing accuracy)
		(Ink consumption):		/1.5 (One square 1.5ml)
		(Ink supply mode):	6-8	(Six to eight color white ink circulation stirring to prevent precipitation)
		(Use ink):	UV	(Uv ink Textile ink uses ink)
		(curing method):	/ UV	(Water-cooled air-cooled UV lamp)
	uv	(uv light power):		100W
		(Platform regulation):	+ /	(Automatic adjustment plus touch screen)
		(size of device):		1370*1200*700mm
		(package size):		1500*1350*880mm
(Number of sprinkler heads):	3 (three)	(outer packing):		(Fumigated export wooden cases)
(Platform material):	(Adsorption platform)	(Power requirement):		AC220/110+1050~60HzP00W
(Printing direction) :	/ (Single item bidirectional printing)			
(Print nozzle) :	(Imported ultra-light print head)	(ink supply system):	/ +	(The software automatically feeds ink Spray and automatic cleaning)
(Color software):	/ / (Meng tai Rui Cai Rui yin)	(OS):		Windows
/ (Net weight, gross weight):	220KG/240KG	(Cylinder function):	(:)	(Support printing cylinder function another option)
(outer packing):	(Fumigated export wooden cases)	(Print color):	+	(White color +gloss oil)

(layout):

TIF、PDF、TIF、GPJ、CAD/CDR



6060	uv	(6060 Left roll right flat UV printer.)	(modle):	6060	uv	(6060 Left roll right flat UV printer.)
			(print size):			60*60CM
			(Crystal scale size):	30CM	*100	(30cm wide and 100m long)
			(print speed):			(Adjustable high and low medium speed)
			(Print height):			0-23CM
			X (X-axis drive):			(Adopt silent guide rail, no noise)
			Y (Y-axis drive):	Y		(Y-axis double guide screw drive improves printing accuracy)
			(Ink consumption):		/1.5	(One square 1.5ml)
			(Ink supply mode):	6-8	(	)(Six to eight color white ink circulation stirring to prevent precipitation)
			(Use ink):		UV	(Uv ink Textile ink uses ink)
			(curing method):		/ UV	(Water-cooled air-cooled UV lamp)
	uv		(uv light power):			100W
			(Platform regulation):		+	(Automatic adjustment plus touch screen)
			(size of device):			1520*1120*720mm
			(package size):			1850*1450*950mm
			(outer packing):			(Fumigated export wooden cases)
			(Power requirement):			AC220/110+1050~60HzP00W
			(Print nozzle):			(Imported ultra-light print head)
			(ink supply system):		/ +	(The software automatically feeds ink Spray and automatic cleaning)
			(Color software):		/ /	(Meng tai Rui Cai Rui yin)
			(OS):			Windows
/			(Net weight, gross weight):			230KG/250KG
			(Cylinder function):		(:)	(Support printing cylinder function another option)
			(outer packing):			(Fumigated export wooden cases)
			(Print color):		+	(White color +gloss oil)
			(layout):			TIF、PDF、TIF、GPJ、CAD/CDR

6090	uv	(6090 upgraded uv printer)	(modle) :	6090-UV	(6090-uv printer)
			(print size):	60*90CM	
			(print speed):	5-10 /	(5~10 square hours)
			(Print height):	0-23CM	
			X (X-axis drive):	(Adopt silent guide rail, no noise)	
			Y (Y-axis drive):	Y	(Y-axis double guide screw drive improves printing accuracy)
			(Ink consumption):	/1.5	(One square 1.5ml)
			(Ink supply mode):	6-8	(Six to eight color white ink circulation stirring to prevent precipitation)
			(Use ink):	UV 、	(Uv ink Textile ink uses ink)
			(curing method):	/ UV	(Water-cooled air-cooled UV lamp)
			uv (uv light power):	120W	
			(Platform regulation):	+ /	(Automatic adjustment plus touch screen)
			(size of device):	1370*1200*700mm	
			(package size):	1500*1350*880mm	
(Number of sprinkler heads):	3	(three)			
(Platform material):	(Adsorption platform)		(outer packing):	(Fumigated export wooden cases)	
(Printing direction) :	/	(Single item bidirectional printing)	(Power requirement):	AC220/110+1050~60HzP00W	
(Print nozzle) :	(Imported ultra-light print head)		(ink supply system):	/ +	(The software automatically feeds ink Spray and automatic cleaning)
(Color software):	/ /	(Meng tai Rui Cai Rui yin)	(OS):	Windows	
/ (Net weight, gross weight):	180KG/200KG		(Cylinder function):	(:) (Support printing cylinder function another option)	
(outer packing):	(Fumigated export wooden cases)		(Printing color (colour)) :	() + + (White+ gloss+ oil)	



6090	uv	(6090 upgraded uv printer with integrated screen rolling.)	(modle):	6090	(6090 roll-flat integrated printer)
			(print size):		60*90CM
			(Crystal scale size):	30CM *100	(30cm wide and 100m long)
			(print speed):		(Adjustable high and low medium speed)
			(Print height):		0-23CM
	X	(X-axis drive):			(Adopt silent guide rail, no noise)
	Y	(Y-axis drive):	Y		(Y-axis double guide screw drive improves printing accuracy)
		(Ink consumption):		/1.5	(One square 1.5ml)
		(Ink supply mode):	6-8	(	(Six to eight color white ink circulation stirring to prevent precipitation)
		(Use ink):		UV	(Uv ink Textile ink uses ink)
		(curing method):		/ UV	(Water-cooled air-cooled UV lamp)
	uv	(uv light power):			100W
		(Platform regulation):		+	(Automatic adjustment plus touch screen)
		(size of device):			1370*1200*700mm
		(package size):			1500*1350*880mm
		(Number of sprinkler heads):	3 (three)		
		(Platform material):	(Adsorption platform)		(Fumigated export wooden cases)
		(Printing direction):	/ (Single item bidirectional printing)		
					(Power requirement): AC220/110+1050~60HzP00W
		(Print nozzle):	(Imported ultra-light print head)	/ +	(The software automatically feeds ink Spray and automatic cleaning)
		(Color software):	/ / (Meng tai Rui Cai Rui yin)		Windows
/		(Net weight, gross weight):	220KG/240KG		(:) (Support printing cylinder function another option)
		(outer packing):	(Fumigated export wooden cases)		+ (White color +gloss oil)
		(layout):			TIF、PDF、TIF、GPJ、CAD/CDR



6090	uv	(6090 Left roll right flat UV printer.)	(modle) :	6090	uv	(6090 Left roll right flat UV printer.)
			(print size):			60*90CM
			(Crystal scale size):		30CM *100	(30cm wide and 100m long)
			(print speed):			(Adjustable high and low medium speed)
			(Print height):			0-23CM
			X (X-axis drive):			(Adopt silent guide rail, no noise)
			Y (Y-axis drive):	Y		(Y-axis double guide screw drive improves printing accuracy)
			(Ink consumption):		/1.5	(One square 1.5ml)
			(Ink supply mode):	6-8	(	)(Six to eight color white ink circulation stirring to prevent precipitation)
			(Use ink):		UV 、 、	(Uv ink Textile ink uses ink)
			(curing method):		/ UV	(Water-cooled air-cooled UV lamp)
	uv		(uv light power):			100W
			(Platform regulation):		+ /	(Automatic adjustment plus touch screen)
			(size of device):			1520*1120*720mm
			(package size):			1850*1450*950mm
		(Number of sprinkler heads):	3/4 (three)			
		(Platform material):	(Adsorption platform)			(outer packing): (Fumigated export wooden cases)
		(Printing direction) :	/ (Single item bidirectional printing)			(Power requirement): AC220/110+1050~60HzP00W
		(Print nozzle) :	(Imported ultra-light print head)		(ink supply system):	/ + (The software automatically feeds ink Spray and automatic cleaning)
		(Color software):	/ / (Meng tai Rui Cai Rui yin)		(OS):	Windows
/		(Net weight, gross weight):	220KG/260KG		(Cylinder function):	(:) (Support printing cylinder function another option)
		(outer packing):	(Fumigated export wooden cases)		(Print color):	+ (White color +gloss oil)
		(layout):				TIF、PDF、TIF、GPJ、CAD/CDR

9060

uv

(9060 upgraded uv
printer)(module)
:

9060-UV

(9060- uv printer)



(print size):

90*60CM

(print speed):

8-14 / (8~14 square hours)

(Print height):

0-23CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

8

(

eight color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

、

、

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

120W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

1520*1120*720mm

(package size):

1600*1200*910mm

(Number of
sprinkler heads):

4 (four)

(Platform material):

(Standard
adsorption platform.)

(outer packing):

(Fumigated export wooden cases)

(Printing
direction) :/ (Single item
bidirectional printing)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported
ultra-light print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic cleaning)

(Color software):

/ / (Meng tai Rui
Cai Rui yin)

(OS):

Windows

/ (Net weight, gross
weight):

220KG/270KG

(Cylinder function):

(:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated export
wooden cases)(Printing color
(colour)) :

+

+

+

/

+

+

+

(White

+

color

+

color

+

smooth oil/White

+

white

+

colorful

+

colorful)

(Nozzle
protection) :

、

(Automatic cleaning, automatic moisturizing.)



9060 uv (9060 upgraded uv printer with flat roll.)

(modle):

9060

(9060 roll-flat integrated printer.)

(print size):

90*60CM

(Crystal scale size):

60CM *100 (60cm wide and 100m long)

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-23CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5 (One square 1.5ml)

(Ink supply mode):

6-8

(

)(Six to eight color white ink circulation stirring to prevent precipitation)

(Use ink):

UV

、

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

1520*1120*720mm

(Number of sprinkler heads):

4

(package size):

1600*1200*910mm

(Platform material):

(Adsorption platform)

:

(Fumigated export wooden cases)

(Printing direction) :

/

(Single item bidirectional printing)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

(Imported ultra-light print head)

(ink supply system):

/

+

(The software automatically feeds ink Spray and automatic cleaning)

(Color software):

/

/

(Meng tai Rui Cai Rui yin)

(OS):

Windows

/

(Net weight, gross weight):

270KG/300KG

(Cylinder function):

(

:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated export wooden cases)

((Print color)) :

+

(White color + gloss oil)

(layout):

TIF、PDF、TIF、GPJ、CAD/CDR

(Nozzle protection) :

(Automatic cleaning, automatic moisturizing.)



1210	uv	(1210 upgraded uv printer)	(modle) :	1210-UV	(1210-uv printer)	
			(print size):	100*120CM		
			(print speed):	10-15 /	(10~15 square hours.)	
			(Print height):	0-40CM		
			(Ink consumption):	/1.5	(One square 1.5ml)	
			(Ink supply mode):	8 (	)(eight color white ink circulation stirring to prevent precipitation)	
			(Use ink):	UV 、 、	(Uv ink Textile ink uses ink)	
			(curing method):	/ UV	(Water-cooled air-cooled UV lamp)	
	uv			(uv light power):	200W	
			(Platform regulation):	(regulate automatically)		
			(size of device):	2300*1400*1420mm		
(Number of sprinkler heads):		4 (four)	(package size):	2350*1500*1570mm		
(Platform material):		(adsorption platform)	(outer packing):	(Fumigated export wooden cases)		
(Printing direction) :		/ (Single item bidirectional printing)	(Power requirement):	AC220/110+1050~60HzP00W		
(Print nozzle) :		(Imported ultra-light print head)	(ink supply system):	/ +	(The software automatically feeds ink Spray and automatic cleaning)	
(Color software):		/ / (Meng tai Rui Cai Rui yin)	(OS):	Windows		
/ (Net weight, gross weight):		380KG/400KG	(Cylinder function):	(:) (Support printing cylinder function another option)		
(outer packing):		(Fumigated export	(Printing colo) :	+ + + / + + + (White +color +color +smooth oil/White +white +colorful +colorful)		



I1600

(Epson i1600 special-shaped product printer)

A2+

(A2+special-shaped product printer)

(modle) :

UV

(High drop uv printer)

(print size):

60*50CM

(print speed):

(Adjustable high and low medium speed)

(Print height):

0-23CM

X

(X-axis drive):

(Adopt silent guide rail, no noise)

Y

(Y-axis drive):

Y

(Y-axis double guide screw drive improves printing accuracy)

(Ink consumption):

/1.5

(One square 1.5ml)

(Ink supply mode):

6-8
precipitation)

(Six to eight color white ink circulation stirring to prevent

(Use ink):

UV

(Uv ink Textile ink uses ink)

(curing method):

/

UV

(Water-cooled air-cooled UV lamp)

uv

(uv light power):

100W

(Platform regulation):

+

/

(Automatic adjustment plus touch screen)

(size of device):

840*980*680mm

(package size):

1100 950 830 mm

(Number of sprinkler heads):

2 (two)

(Platform material):

/

(Steel adsorption platform

(outer packing):

(Fumigated export wooden cases)

(Printing direction) :

/

(Single item bidirectional printing)

(Power requirement):

AC220/110+1050~60HzP00W

(Print nozzle) :

i1600(Epson i1600)

(ink supply system):

/ +
cleaning)

(The software automatically feeds ink Spray and automatic

(Color software):

/

/

(Meng tai Rui Cai Rui yin)

(OS):

Windows

/ (Net weight, gross weight): 80KG/130KG

(Cylinder function):

(

:

)

(Support printing cylinder function another option)

(outer packing):

(Fumigated export wooden cases)

(Printing colo) :

+

(White color +gloss oil)

(layout):

TIF、PDF、TIF、jpg、CAD、CDR、

(Nozzle protection) :

、

(Automatic cleaning, automatic moisturizing.)



1613UV

Technical parameter		
1613	Model number	1613
1600mm() x 1300mm ()	Print size	1600 mm (width) x 1300 MM (length)
	Nozzle configuration	Seiko Epson` s 10 generation showerhead
4 ()	Number of nozzles	4 nozzle configuration (white color)
0—250MM	Print Height	0—250MM
	Nozzle protection	Automatic ink station MOISTURIZER
150KG	Print weight	Non—destructive precision weight 150KG
2880dpi*1440dpi*720dpi*360dpi	Print accuracy	2880dpi*1440dpi*720dpi*360dpi
4 +1 +1	Ink System	4 color 1 white 1 V
10m²/H 6m²/H 4m²/H	Print speed	The printing speed is 10 M2/h 6 m2/h 4 m2/h
TIFF (RGB&CMYK)、BMP、PDF、EPS、JPEG	Receiving file	TIFF (RGB & CMYK) , BMP, PDF, EPS, JPEG, etc.
AC220—240V, 50Hz, 2000W	Power requirement	AC220—240V, 50Hz, power consumption of 2000W
USB2.0 ,	Interface mode	USB2.0 and network interface, image transmission using fiber transmission
MicrosoftWindows98/Me /2000 /Win7/win8	Operating Platform	MicrosoftWindows98/Me /2000 /Win7/win8
UltraPrint () RIP	Software output	Rip Software Montaigne
: 18℃—35℃ , 40%—80%	Working Environment	Optimum temperature: 18 ° c—35 ° C, relative humidity 40%—80%
500KG	Equipment Weight	500KG
2.830*1.920*1.250 (x x)	Equipment size	2830MM * 1920MM * 1250MM (length x width x height)
() ,	Warranty period	Warranty for three year (not guaranteed ink road access and Sprinkler) , life—long paid maintenance
UV Ink		SPECIAL ANTI—BLOCKING HIGH QUALITY UV ink



2513UV

2513uv printer

Technical parameter		
2513	Model number	2513
2500mm() x 1300mm ()	Print size	2500 mm (width) x 1300 MM (length)
	Nozzle configuration	Seiko Epson' s 10 generation showerhead
4 (+)	Number of nozzles	4 nozzle configuration (white color)
0—250MM	Print Height	0—250MM
	Nozzle protection	Automatic ink station MOISTURIZER
150KG	Print weight	Non—destructive precision weight 150KG
2880dpi*1440dpi*720dpi*360dpi	Print accuracy	2880dpi*1440dpi*720dpi*360dpi
4 +1 +1*	Ink System	4 color 1 white 1 V
10m²/H 6m²/H 4m²/H	Print speed	The printing speed is 10 M2/h 6 m2/h 4 m2/h
TIFF (RGB&CMYK)、BMP、PDF、EPS、JPEG	Receiving file	TIFF (RGB & CMYK) , BMP, PDF, EPS, JPEG, etc.
AC220—240V, 50Hz, 2000W	Power requirement	AC220—240V, 50Hz, power consumption of 2000W
USB2.0 ,	Interface mode	USB2.0 and network interface, image transmission using fiber transmission
MicrosoftWindows98/Me /2000 /Win7/win8	Operating Platform	MicrosoftWindows98/Me /2000 /Win7/win8
UltraPrint () RIP	Software output	Rip Software Montaigne
: 18°C—35°C , 40%—80%	Working Environment	Optimum temperature: 18 ° c—35 ° C, relative humidity 40%—80%
600KG	Equipment Weight	600KG
3800MM*2150MM*1250MM (x x)	Equipment size	4200MM * 1950MM * 1300MM (length x width x height)
() ,	Warranty period	Warranty for three year (not guaranteed ink road access and Sprinkler) , life—long paid maintenance
uv	Ink	SPECIAL ANTI—BLOCKING HIGH QUALITY UV ink
	Production process	A professional engineer trains the printer to operate until the desired product is completed
,	Workshop Construction	Professional Engineer Planning and design, to provide full guidance
	Operator training	Train customer operator to be familiar with the operation



3020UV

3020uv printer

Technical parameter		
3020	Model number	3020
3000mm() x 2000mm ()	Print size	3000 mm (width) x 2000 MM (length)
	Nozzle configuration	Seiko Epson´ s 10 generation showerhead
4 (+)	Number of nozzles	4 nozzle configuration (white color)
0—250MM	Print Height	0—250MM
	Nozzle protection	Automatic ink station MOISTURIZER
150KG	Print weight	Non—destructive precision weight 150KG
2880dpi*1440dpi*720dpi*360dpi	Print accuracy	2880dpi*1440dpi*720dpi*360dpi
4 +1 +1*	Ink System	4 color 1 white 1 V
10m²/H 6m²/H 4m²/H	Print speed	The printing speed is 10 M2/h 6 m2/h 4 m2/h
TIFF (RGB&CMYK)、BMP、PDF、EPS、JPEG	Receiving file	TIFF (RGB & CMYK) , BMP, PDF, EPS, JPEG, etc.
AC220—240V, 50Hz, 2000W	Power requirement	AC220—240V, 50Hz, power consumption of 2000W
USB2.0 ,	Interface mode	USB2.0 and network interface, image transmission using fiber transmission
MicrosoftWindows98/Me /2000 /Win7/win8	Operating Platform	MicrosoftWindows98/Me /2000 /Win7/win8
UltraPrint () RIP	Software output	Rip Software Montaigne
: 18°C—35°C , 40%—80%	Working Environment	Optimum temperature: 18 ° c—35 ° C, relative humidity 40%—80%
600KG	Equipment Weight	600KG
4700MM*2700MM*1300MM (x x)	Equipment size	4700MM*2700MM*1300MM (length x width x height)
() ,	Warranty period	Warranty for three year (not guaranteed ink road access and Sprinkler) , life—long paid maintenance
uv	Ink	SPECIAL ANTI—BLOCKING HIGH QUALITY UV ink
	Production process	A professional engineer trains the printer to operate until the desired product is completed
,	Workshop Construction	Professional Engineer Planning and design, to provide full guidance
	Operator training	Train customer operator to be familiar with the operation



(product name) :	8D(Intelligent industrial floor painting machine.)					
(Eipment typequ) :	(Integrated Industrial Machine)					
(unit type) :	HDX—5060(Five—O.)					
(Use paint) :	(Environmentally—friendly customized oil—based pigments for ground machines.)					
(Motherboard configuration) :	8	CPU8GB	3.0USB(Octa Core High Speed	High speed memory)		
(nozzle type) :	(Super Clear Epson Print Head Imported from Japan)					
(Printing accuracy) :	360dpi720dpi1440dpi2880dpi5760dpi()					
(Appearance size) :	450mm	500mm	900mm (	)	(450 mm long.500 mm wideHeight 900 mm Dimensions after folding)	
(Print frame) :	2500*6000mm/3000*6000mm () (Can be extended indefinitely.)					
(printing speed) :	5—15m²/	10—25m²/	(Ordinary 5 ~ 15 square meters./High speed hours.10 to 25 square meters per hour.)			
(Print color) :	CMYK/(W)	(	(Can be customized w Customizable blue, red, yellow and black. Can be customized in white)			
(Voltage requirements.) :	220v	(	110v	)	50HZ/60HZ(Household electricity220v110V is also available.Or 50HZ 60HZ)	
(Environmental requirements) :	: —30℃—40℃	:	0—6	(Temperature.—30℃—40℃Wen Fengfeng 0—6level Rain and snow weather prohibit construction to prevent electric shock.)		
(Power consumption) :	100W	300W(No load 100 watts. Maximum 300 watts at operation.)				
(Sprinkler maintenance) :	,	,	,	(No need to disassemble, no need to clean, automatic cleaning, automatic moisturizing.)		
(Probe telescopic) :	0—10cm(Effective expansion range 0 ~ 10 cm)					
(Scope of application) :	floor, and so on), , , , ,(Epoxy floor paint floor, glass floor, latex paint floor, tile floor, lime floor, cement					
(Image format) :	AI/CDR/PSD/GIF/TIFF/JPEG/BMP (And so on. Common image formats)					
(Control mode) :	U	(Plug U disk wireless operation)				
Control system.) :	WIN7、 WIN10、 XP()					
(Language selection) :	/	/	(Chinese / English / Customize any national language)			
(Additional Features) :	,	,	,	(Can achieve power life, automatic jump white printing, seamless splicing, infrared positioning)		
(Fold size) :	400*700*1500 () (Support for Customization)					
(Airframe weight) :	30kg					

(product name) :	8D (8DIntelligent industrial painting machine.)		
(Eipment typequ) :	(Industrial control all—in—one computer)		
(unit type) :	HDX—2560		
(Use paint) :	(Environmentally Friendly Customized Oil Pigments for Walls)		
(Motherboard configuration) :	8	CPU 8GB	3.0USB (Octa Core High Speed High speed memory)
(nozzle type) :	(Super Clear Epson Print Head Imported from Japan)		
(Printing accuracy) :	360dpi 720dpi 1440dpi 2880dpi 5760dpi (360dpi 720dpi 1440dpi 2880dpi 5760dpi)		
(Appearance size) :	600mm	500mm	1250mm () (L 600 mm W 500 mm H 1250 mm Folded dimensions)
(Print frame) :	2500*6000mm/3000*6000mm () (Can be extended indefinitely)		
(printing speed) :	5—15 m²/	10—25 m²/	(Ordinary 5 ~ 15 square meters./High speed hours.10 to 25 square meters per hour)
(Print color) :	CMYK/(W)	()	(Can be customized w Customizable blue, red, yellow and black. Can be customized in white)
(Voltage requirements.) :	220v	(110v)	50HZ/60HZ ((Household electricity220v110V is also available.Or 50HZ 60HZ)
(Environmental requirements) :	: —30℃—40℃ (Temperature.—30℃—40℃)		
() :	: 0—6	(0—6level Rain and snow weather prohibit construction to prevent electric shock.)	
(Power consumption) :	100W	300W	(No load 100 watts. Maximum 300 watts at operation)
(Sprinkler maintenance) :	、	、	(No need to disassemble, no need to clean, automatic cleaning, automatic moisturizing)
(Probe telescopic) :	0—10cm (Effective expansion range 0 ~ 10 cm)		
(Scope of application) :	so on)、 、 、 ° 、 、 (Tiles, glass walls, latex paint walls, diatom mud walls, white walls, putty walls, and		
(Image format) :	AI/CDR/PSD/GIF/TIFF/JPEG/BMP (And so on. Common image formats)		
(Control mode) :	U (Plug U disk wireless operation)		
(Control system) :	WIN7、 WIN10、 XP		
(Language selection) :	/ / (Chinese / English / Customize any national language)		
(Additional Features) :	、 、 、 (Can achieve power life, automatic jump white printing, seamless splicing, infrared positioning)		
(Fold size) :	400*700*1500 () (Support for Customization)		
(Airframe weight) :	40kg		
(Carrying and handling) :	、 、 。 SUV、 ((Folding can be carried, no need to disassemble, car, suv, van can be)		

