



Yongkang Liqian Industry and Trade Co., Ltd.

PRODUCT MANUAL

YONGKANG LIQIAN INDUSTRY AND TRADE CO.,LTD.

About Our Company



COMPANY INTRODUCTION

YONGKANG LIQIAN INDUSTRY AND TRADE CO.,LTD. Was established in 2007. It is a Sino-Sweden joint venture and export-oriented enterprise specialized in manufacturing Mini Jeep (for kids & adults), Tricycle (TR trike, 3-wheel Motorcycle), Vintage Car, All Terrain Vehicle (ATV, Snow ATV, Quad Bike, Farm ATV with trailer), UTV, Dirt Bike (Monkey dirt bike), Go Kart (F1 Racing kart, Rental Go Kart, Snow Go Kart), etc., all kinds of gas-powered and electricity-powered vehicles. It occupies more than 60000 square meter factory and boasts more than 500 workers including about 50 managerial staffs. It has its own machining workshop, frame welding workshop, engine production workshop, assembling workshop, packing workshop, testing system.

Its assembling workshop is equipped with three half-automatic assembling production lines. We have the production capacity of producing one 40HC per day. We have always been paying special importance to the parts quality, assembling control, packing control, loading control and the invention of new models. We have stable parts suppliers, have well-trained and stable employee. Before packing, we have our every bike drove, inspected by experienced inspectors. We have our own fork truck for loading plus experienced loading team in order to avoid any loading damages.





ZTR

MINI
VINTAGE
CAR



ZTR 350CC

BASIC PARAMETER

Product size	2850*1630*770mm	Max Loading	240kgs
Seat Height	200mm	Packing Size	2850*1140*730mm
Wheel Base	1450mm	G.W/N.W	300kgs/270kgs
Ground Clearance	130mm	Container Loads	12pcs/20FT, 24pcs/40HQ

ENGINE&DRIVETRAIN

Engine	350CC water-cooling, 4 VALVE ,with balance shaft
Cooling System	Water Cooled
Fuel Type	#92+ Gasoline

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V14Ah)	Rear Tire	270/30-14
Drive Type	shaft drive transission	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	120km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	145/30-14		

ETR ELECTRIC

BASIC PARAMETER

Product size	2850*1630*770mm	Max Loading	240kgs
Seat Height	200mm	Packing Size	2850*1140*730mm
Wheel Base	1450mm	G.W/N.W	350kgs/320kgs
Ground Clearance	130mm	Container Loads	12pcs/20FT, 24pcs/40HQ

ENGINE&DRIVETRAIN

Battery (lithium battery)	6000W 72V 80AH
	10000W 72V120AH
	12000W 72V150AH

BRAKE&TRANSMISSION

Starting System	Electrical Start	Rear Tire	270/30-14
Drive Type	Motor direct drive at rear axle	Front Suspension	Front Dual Shock Absorber
Transmission	H, L, N, R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	120km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	145/30-14		



GAS-POWER

BASIC PARAMETER

Product size	1900*1150*950mm	Max Loading	250kgs
Seat Height	480mm	Packing Size	1920*1100*530mm
Wheel Base	1240mm	G.W/N.W	155kgs/130kgs
Ground Clearance	180mm	Container Loads	24pcs/20FT, 58pcs/40HQ

ENGINE&DRIVETRAIN

Engine	110/125cc, Air Cooled, 4-Stroke, Single Cylinder
Cooling System	Air / Water Cooled
Fuel Type	#92+ Gasoline

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V5Ah)	Rear Tire	16x8-7
Drive Type	Chain Drive	Front Suspension	Independent double shock absorber
Transmission	3.2.1 N.R	Rear Suspension	Independent double shock absorber
Max speed	60km/h	Front Brake	Hydraulic disc
Rim Material	Steel/Aluminum Rim	Rear Brake	Hydraulic disc
Front Tire	16x8-7		

ELECTRIC

BASIC PARAMETER

Product size	1900*1150*950mm	Max Loading	250kgs
Seat Height	480mm	Packing Size	1920*1100*530mm
Wheel Base	1240mm	G.W/N.W	155kgs/130kgs
Ground Clearance	180mm	Container Loads	24PCs/20FT, 58pcs/40HQ

ENGINE&DRIVETRAIN

Motor	800W Permanent magnet brushless motor
Battery	800W 48V 20AH(Lead-acid)

BRAKE&TRANSMISSION

Charger time	5-6 hours	Rear Tire	16x8-7
Drive Type	shaft drive transission	Front Suspension	Independent double shock absorber
Transmission	H, L, N, R	Rear Suspension	Independent double shock absorber
Max Speed	50m/h	Front Brake	Hydraulic disc
Range	25km	Rear Brake	Hydraulic disc
Rim Material	Steel/Aluminum Rim		
Front Tire	16x8-7		

200CC
JEEP



JEEP



200CC GAS-POWER

BASIC PARAMETER			
Product size	2360*1300*1600mm	Max Loading	200kgs
Seat Height	660mm	Packing Size	2300*1380*750mm
Wheel Base	1240mm	G.W/N.W	400kgs/380kgs
Ground Clearance	220mm	Container Loads	12pcs/20FT, 27pcs/40HQ
ENGINE&DRIVETRAIN			
Engine	200cc 4 Stroke, 1 Cylinder		
Cooling System	Air Cooled		
Fuel Type	#92+ Gasoline		
BRAKE&TRANSMISSION			
Starting System	Electrical Start (12V15Ah)	Rear Tire	25X10-12
Drive Type	Chain Drive	Front Suspension	Front Dual Shock Absorber
Transmission	D, N, R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	65km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	25X8-12		

320CC GAS-POWER

BASIC PARAMETER			
Product size	2900*1520*1620mm	Max Loading	500kgs
Seat Height	1000mm	Packing Size	2700*1400*960mm
Wheel Base	1240mm	G.W/N.W	480kgs/450kgs
Ground Clearance	220mm	Container Loads	8pcs/20FT, 18pcs/40HQ
ENGINE&DRIVETRAIN			
Engine	320CC 4 Stroke, 1 Cylinder 4X4		
Cooling System	Water Cooled		
Fuel Type	#92+ Gasoline		
BRAKE&TRANSMISSION			
Starting System	Electrical Start	Rear Tire	25X10-12
Drive Type	Shaft Drive	Front Suspension	Front Dual Shock Absorber
Transmission	D.N.R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	70km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	25X8-12		



2X2
4X4



LQ-JP GAS-POWER

BASIC PARAMETER			
Product size	2000*1000*740mm	Max Loading	240kgs
Seat Height	650mm	Packing Size	1920*1230*500mm
Wheel Base	1240mm	G.W/N.W	200kgs/180kgs
Ground Clearance	100mm	Container Loads	24pcs/20FT, 58pcs/40HQ
ENGINE&DRIVETRAIN			
Engine	110cc/125cc/150cc 4 Stroke, 1 Cylinder		
Cooling System	Air/Water Cooled		
Fuel Type	#92+ Gasoline		
BRAKE&TRANSMISSION			
Starting System	Electrical Start (12V9Ah)	Rear Tire	4.80-R8
Drive Type	Chain Drive	Front Suspension	Front Dual Shock Absorber
Transmission	3,2,1 N, R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	55km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	4.80-R8		

LQ-EJP ELECTRIC

BASIC PARAMETER			
Product size	2000*1000*740mm	Max Loading	240kgs
Seat Height	660mm	Packing Size	1920*1230*500mm
Wheel Base	1240mm	G.W/N.W	200kgs/180kgs
Ground Clearance	100mm	Container Loads	24pcs/20FT, 58pcs/40HQ
ENGINE&DRIVETRAIN			
Battery	800W 48V 20AH(Lead-acid)		
	1200W 60V 20AH (Lead-acid)		
	1200W 60V 42AH (Lithium)		
BRAKE&TRANSMISSION			
Starting System	Electrical Start	Rear Tire	4.80-R8
Drive Type	shaft drive transission	Front Suspension	Front Dual Shock Absorber
Transmission	H, L, N, R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	40km/h-60km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	4.80-R8		



ELECTRIC-VINTAGE-CAR

BASIC PARAMETER			
Product size	2310*1260*880mm	Max Loading	230kgs
Seat Height	730 mm	Packing Size	2300*1300*730mm
Wheel Base	1300mm	G.W/N.W	288kgs/273kgs
Ground Clearance	430mm	Container Loads	12pcs/20FT, 24pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor choice	1500W/2000W/3000W,Permanent magnet synchronous motor	Rim Material	Aluminum Rim
Battery	1500W 72V 20AH(Lead-acid) 2000W 72V 60AH(Lithium battery) 3000W 72V 80AH(Lithium battery)	Front Tire	145/7-12
		Rear Tire	145/7-12
Charger time	3-8 hours	Front Suspension	Independent double shock absorber
Drive Type	H,L,N,R	Rear Suspension	Independent double shock absorber
Transmission	shaft drive transission	Front Brake	hydraulic disc and handle park brake
Max Speed	65km/h	Rear Brake	hydraulic disc and handle park brake
Range	Range 30-40Km(20AH)/ 50-60Km(60AH)/ 70-80km(80AH)		

LQ-E005



BASIC PARAMETER			
Product size	1970*1180*870mm	Max Loading	260kgs
Seat Height	900mm	Packing Size	1910*1100*780mm
Wheel Base	1350mm	G.W/N.W	291kgs/265kgs
Ground Clearance	300mm	Container Loads	18pcs/20FT, 36pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor choice	72V 5000W - 72V3000W DC Brushless motor (bldc motor)	Rim Material	Aluminum Tires
Battery	72V 62AH lithium battery 72V 85AH lithium battery	Front Tire	23*7-10
		Rear Tire	22*10-10
Controller	intelligent controller,use bluetooth cnetct to phone	Front Suspension	hydraulic suspension
		Rear Suspension	hydraulic suspension
Charger time	3-6 hours	Front Brake	front/manual
Transmission	shaft drive transission	Rear Brake	rear/foot
Max Speed	55km/h 3000W , 60km/h 5000W		



KART
GAS
POWER

ELECTRIC



LQ-GK125 GAS-POWER

BASIC PARAMETER

Product size	2100*1270*1290mm	Max Loading	180kgs
Seat Height	450mm	Packing Size	1950*1100*700mm
Wheel Base	1120(Front)/1080(rear)	G.W/N.W	180kgs/160kgs
Ground Clearance	130mm	Container Loads	18pcs/20FT, 36pcs/40HQ

ENGINE&DRIVETRAIN

Engine	125cc 4 Stroke, 1 Cylinder
Cooling System	Air Cooled
Fuel Consumption	4L/100KM
Fuel Type	#92+ Gasoline

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V9Ah)	Rear Tire	4.80-R8
Drive Type	428 Chain Drive	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	55km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	4.80-R8		



LQ-EGK A ELECTRIC

BASIC PARAMETER

Product size	2100*1270*1290mm	Max Loading	180kgs
Seat Height	450mm	Packing Size	1950*1100*700mm
Wheel Base	1120(Front)/1080(rear)	G.W/N.W	180kgs/160kgs
Ground Clearance	130mm	Container Loads	18pcs/20FT, 36pcs/40HQ

ENGINE&DRIVETRAIN

Battery	750W 60V 20AH (Lead-acid) 40km
---------	--------------------------------

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V9Ah)	Rear Tire	4.80-R8
Drive Type	Shaft Drive	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	25-45km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	4.80-R8		



LQ-GK200 GAS-POWER

BASIC PARAMETER

Product size	2550*1550*1480mm	Max Loading	200kgs
Seat Height	450mm	Packing Size	2350*1420*880mm
Wheel Base	1760mm	G.W/N.W	260kgs/200kgs
Ground Clearance	260mm	Container Loads	6pcs/20FT, 21pcs/40HQ

ENGINE&DRIVETRAIN

Engine	200cc4 Stroke, 1 Cylinder
Cooling System	Air/Water Cooled
Fuel Consumption	4.2L/100KM
Fuel Type	#92+ Gasoline

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V9Ah)	Rear Tire	16*8-7
Drive Type	Chain transmission	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	40km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	16*8-7		



LQ-EGK B ELECTRIC

BASIC PARAMETER

Product size	2550*1550*950mm	Max Loading	200kgs
Seat Height	450mm	Packing Size	2350*1420*880mm
Wheel Base	1760mm	G.W/N.W	260kgs/200kgs
Ground Clearance	260mm	Container Loads	24PCs/20FT, 58pcs/40HQ

ENGINE&DRIVETRAIN

Battery	1500W 60v 52AH (Lead-acid) 40km 2200W 72v 52AH (Lead-acid) 60km 5000W 72V 150AH (Lithium) 80km
---------	--

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V9Ah)	Rear Tire	16*8-7
Drive Type	Shaft Drive	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	40-55km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	16*8-7		



LQ-GK300 GAS-POWER (Four-wheel independent suspension)

BASIC PARAMETER

Product size	2550*1550*1480mm	Max Loading	300kgs
Seat Height	450mm	Packing Size	2350*1420*880mm
Wheel Base	1760mm	G.W/N.W	350kgs/320kgs
Ground Clearance	260mm	Container Loads	6pcs/20FT, 21pcs/40HQ

ENGINE&DRIVETRAIN

Engine	200cc4 Stroke, 1 Cylinder
Cooling System	Water Cooled
Fuel Consumption	5L/100KM
Fuel Type	#92+ Gasoline

BRAKE&TRANSMISSION

Starting System	Electrical Start (12V9Ah)	Rear Tire	10 inch10 inch
Drive Type	Chain + shaft transmission	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	70km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	10 inch		



LQ-ELY ELECTRIC

BASIC PARAMETER

Product size	1800*1150*1230mm	Max Loading	1830*1100*670mm
Seat Height	450mm	Packing Size	350kgs/320kgs
Wheel Base	1480mm	G.W/N.W	155kgs/145kgs
Ground Clearance	200mm	Container Loads	28pcs/20FT, 60pcs/40HQ

ENGINE&DRIVETRAIN

Battery	500W 48V 20AH (Lead-acid) 40km
---------	--------------------------------

BRAKE&TRANSMISSION

Charging	6 hours	Rear Tire	7 inch
Drive Type	Differential rear wheel driving	Front Suspension	Front Dual Shock Absorber
Transmission	D,N,R	Rear Suspension	Rear Dual Shock Absorber
Max Speed	55km/h	Front Brake	Dual Hydraulic Disc Brake
Rim Material	Steel/Aluminum Rim	Rear Brake	Dual Hydraulic Disc Brake
Front Tire	6 inch		





500CC
ATV



LQ500-A

BASIC PARAMETER

Product size	2050*1160*1200mm	Max Loading	350kgs
Seat height	980 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	390kgs/365kgs
Ground clearance	350mm	Container loads	12pcs/20FT, 27pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	500cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		



4X4

500CC
ATV



4X4

LQ500-B

BASIC PARAMETER

Product size	2050*1160*1200mm	Max Loading	350kgs
Seat height	980 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	390kgs/365kgs
Ground clearance	350mm	Container loads	12pcs/20FT, 27pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	500cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		



4X4

LQ500-C

BASIC PARAMETER

Product size	2050*1160*1200mm	Max Loading	350kgs
Seat height	980 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	390kgs/365kgs
Ground clearance	350mm	Container loads	12pcs/20FT, 27pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	500cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		

LQ500-D

BASIC PARAMETER

Product size	2050*1160*1200mm	Max Loading	350kgs
Seat height	980 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	390kgs/365kgs
Ground clearance	350mm	Container loads	12pcs/20FT, 27pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	500cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		



4X4



400CC
ATV



LQ400-A



BASIC PARAMETER			
Product size	2050*1160*1200mm	Max Loading	200kgs
Seat height	900 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	350kgs/325kgs
Ground clearance	300mm	Container loads	12pcs/20FT, 27pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	400cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		

LQ400-B



BASIC PARAMETER			
Product size	2050*1160*1200mm	Max Loading	200kgs
Seat height	900 mm	Packing size	2000*1150*850mm
Wheel base	1400mm	G.W/N.W	350kgs/325kgs
Ground clearance	300mm	Container loads	12pcs/20FT, 27pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	400cc 4 Stroke, 1 Cylinder	Rim Material	Aluminum rim
	Water Cooled	Tyre Front	25x8-12
Gasoline	#92up	Tyre Rear	25x10-12
Bore&Stroke	92*75mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V15Ah)	Suspension Rear	Rear dual shock absorber
Drive	Shaft drive	Brakes Front	Dual Hydraulic Disc Brake
Transmission	H,L,N,P,R	Brakes Rear	Dual Hydraulic Disc Brake
Max speed	80km/h		

200CC
ATV



LQ200-A



BASIC PARAMETER			
Product size	1720*1080*1100mm	Max Loading	150kgs
Seat height	840 mm	Packing size	1620*1020*740mm
Wheel base	1180mm	G.W/N.W	220kgs/190kgs
Ground clearance	300mm	Container loads	18pcs/20FT, 42pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	200cc GY6 4 Stroke 1 cylinder air/oil-cooled	Rim Material	Aluminum
		Tyre Front	23×7-10
Gasoline	#92up	Tyre Rear	22×10-10
Bore&Stroke	62.5*57.8mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V 9Ah)	Suspension Rear	Rear shock absorber
Drive	Chain drive	Brakes Front	Front Hydraulic Disc Brake
Transmission	Automatic	Brakes Rear	Rear Hydraulic Disc Brake
Max speed	70km/h		

LQ200-B



BASIC PARAMETER			
Product size	1720*1080*1100mm	Max Loading	150kgs
Seat height	840 mm	Packing size	1620*1020*740mm
Wheel base	1180mm	G.W/N.W	220kgs/190kgs
Ground clearance	300mm	Container loads	18pcs/20FT, 42pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	200cc GY6 4 Stroke 1 cylinder air/oil-cooled	Rim Material	Aluminum
		Tyre Front	23×7-10
Gasoline	#92up	Tyre Rear	22×10-10
Bore&Stroke	62.5*57.8mm	Suspension Front	Front dual shock absorber
StartingDrive	Electrical Start (12V 9Ah)	Suspension Rear	Rear shock absorber
Drive	Chain drive	Brakes Front	Front Hydraulic Disc Brake
Transmission	Automatic	Brakes Rear	Rear Hydraulic Disc Brake
Max speed	70km/h		



200CC
ATV



LQ200-C

BASIC PARAMETER			
Product size	1720*1080*1100mm	Max Loading	150kgs
Seat height	840 mm	Packing size	1620*1080*740mm
Wheel base	1180mm	G.W/N.W	220kgs/190kgs
Ground clearance	300mm	Container loads	18pcs/20FT, 42pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	200cc GY6 4 Stroke 1 cylinder air/oil-cooled	Rim Material	Aluminum
Gasoline	#92up	Tyre Front	23×7-10
Bore&Stroke	62.5*57.8mm	Tyre Rear	22×10-10
StartingDrive	Electrical Start (12V 9Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	Automatic	Brakes Front	Front Hydraulic Disc Brake
Max speed	70km/h	Brakes Rear	Rear Hydraulic Disc Brake



LQ200-D

BASIC PARAMETER			
Product size	1720*1080*1100mm	Max Loading	150kgs
Seat height	840 mm	Packing size	1620*1080*740mm
Wheel base	1180mm	G.W/N.W	220kgs/190kgs
Ground clearance	300mm	Container loads	18pcs/20FT, 42pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	200cc GY6 4 Stroke 1 cylinder air/oil-cooled	Rim Material	Aluminum
Gasoline	#92up	Tyre Front	23×7-10
Bore&Stroke	62.5*57.8mm	Tyre Rear	22×10-10
StartingDrive	Electrical Start (12V 9Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	Automatic	Brakes Front	Front Hydraulic Disc Brake
Max speed	70km/h	Brakes Rear	Rear Hydraulic Disc Brake



LQ200-E

BASIC PARAMETER			
Product size	1720*1080*1100mm	Max Loading	150kgs
Seat height	840 mm	Packing size	1620*1080*740mm
Wheel base	1180mm	G.W/N.W	220kgs/190kgs
Ground clearance	300mm	Container loads	18pcs/20FT, 42pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	200cc GY6 4 Stroke 1 cylinder air/oil-cooled	Rim Material	Aluminum
Gasoline	#92up	Tyre Front	23×7-10
Bore&Stroke	62.5*57.8mm	Tyre Rear	22×10-10
StartingDrive	Electrical Start (12V 9Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	Automatic	Brakes Front	Front Hydraulic Disc Brake
Max speed	70km/h	Brakes Rear	Rear Hydraulic Disc Brake

125CC
ATV





125CC
ATV



LQ125-A

BASIC PARAMETER

Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	730 mm	Packing size	1370*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	40pcs/20FT, 100pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-B

BASIC PARAMETER

Product size	1450*900*980mm	Max Loading	100kgs
Seat height	650 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	200mm	Container loads	45pcs/20FT, 108pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-C

BASIC PARAMETER

Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1370*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	40pcs/20FT, 100pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake

125CC
ATV



LQ125-D

BASIC PARAMETER

Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	750 mm	Packing size	1370*760*600mm
Wheel base	1020mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	40pcs/20FT, 100pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-E

BASIC PARAMETER

Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	750 mm	Packing size	1460*840*620mm
Wheel base	1020mm	G.W/N.W	140kgs/120kgs
Ground clearance	300mm	Container loads	40pcs/20FT, 100pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-F

BASIC PARAMETER

Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1240*760*620mm
Wheel base	1000mm	G.W/N.W	120kgs/100kgs
Ground clearance	270mm	Container loads	50pcs/20FT, 118pcs/40HQ

ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



125CC
ATV



LQ125-G

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-H

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-I

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake

125CC
ATV



LQ125-J

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-K

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-L

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-M

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	270mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-N

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	720 mm	Packing size	1320*760*600mm
Wheel base	1000mm	G.W/N.W	140kgs/120kgs
Ground clearance	200mm	Container loads	45pcs/20FT, 108pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-O

BASIC PARAMETER			
Product size	1500*900*1000mm	Max Loading	100kgs
Seat height	750 mm	Packing size	1460*840*620mm
Wheel base	1020mm	G.W/N.W	140kgs/120kgs
Ground clearance	300mm	Container loads	40pcs/20FT, 100pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc 4 Stroke, Single cylinder air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	19*7-8
Bore&Stroke	52.4*57.8mm	Tyre Rear	18*9.5-8
StartingDrive	Electric Start (12V 5Ah)	Suspension Front	Front dual shock absorber
Drive	Chain drive	Suspension Rear	Rear shock absorber
Transmission	D-N-R	Brakes Front	Hydraulic Disc Brake
Max speed	60km/h	Brakes Rear	Hydraulic Disc Brake





49CC
ATV



LQ49-A

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-B

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ149-C

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake

49CC
ATV



LQ49-D

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-E

BASIC PARAMETER

Product size	1100*650*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	1050*620*520mm
Wheel base	720mm	G.W/N.W	43kgs/48kgs
Ground clearance	140mm	Container loads	75pcs/20FT, 205pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ149-F

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake





49CC
ATV



LQ49-G

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-H

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-I

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake

49CC
ATV



LQ49-J

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-K

BASIC PARAMETER

Product size	1100*650*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	1050*620*520mm
Wheel base	720mm	G.W/N.W	43kgs/48kgs
Ground clearance	140mm	Container loads	75pcs/20FT, 205pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake



LQ49-L

BASIC PARAMETER

Product size	1000*630*660mm	Max Loading	50kgs
Seat height	500mm	Packing size	990*580*490mm
Wheel base	700mm	G.W/N.W	38kgs/43kgs
Ground clearance	140mm	Container loads	88pcs/20FT, 240pcs/40HQ

ENGINE&DRIVETRAIN

BRAKE&TRANSMISSION

Engine	49cc 2 Stroke, single-cylinder air-cooled	Rim Material	iron
Gasoline	25:1 fuel mixture	Tyre Front	13*5-6
Bore&Stroke	44*32.8mm	Tyre Rear	4.10-6
StartingDrive	Pull Start	Suspension Front	Spring shock absorber
Drive	Chain Drive	Suspension Rear	Spring shock absorber
Transmission	Automatic	Brakes Front	Mechanical disc brake
Max speed	30km/h	Brakes Rear	Mechanical disc brake





Gas-powered
dirt bike



Gas-powered
dirt bike



LQ300-B

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	300cc Single-cylinder	Rim Material	Iron or aluminum
	4-stroke Air-cooled	Tyre Front	80/100-21
Gasoline	#92up	Tyre Rear	110/100-18
Bore&Stroke	77*52mm	Suspension Front	Front Dual Shock absorber
StartingDrive	Kick Start(Electric)	Suspension Rear	Rear Single Spring Shock absorber
Drive	Chain Drive		
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake



LQ250-A

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	250cc Single-cylinder	Rim Material	Iron or aluminum
	4-stroke Air-cooled	Tyre Front	80/100-21
Gasoline	#92up	Tyre Rear	110/100-18
Bore&Stroke	77*52mm	Suspension Front	Front Dual Shock absorber
StartingDrive	Kick Start(Electric)	Suspension Rear	Rear Single Spring Shock absorber
Drive	Chain Drive		
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake



LQ300-A

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	300cc Single-cylinder	Rim Material	Iron or aluminum
	4-stroke Air-cooled	Tyre Front	80/100-21
Gasoline	#92up	Tyre Rear	110/100-18
Bore&Stroke	77*52mm	Suspension Front	Front Dual Shock absorber
StartingDrive	Kick Start(Electric)	Suspension Rear	Rear Single Spring Shock absorber
Drive	Chain Drive		
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake



LQ250-B

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	250cc Single-cylinder	Rim Material	Iron or aluminum
	4-stroke Air-cooled	Tyre Front	80/100-21
Gasoline	#92up	Tyre Rear	110/100-18
Bore&Stroke	77*52mm	Suspension Front	Front Dual Shock absorber
StartingDrive	Kick Start(Electric)	Suspension Rear	Rear Single Spring Shock absorber
Drive	Chain Drive		
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake





Gas-powered
dirt bike



LQ250-C

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	250cc Single-cylinder 4-stroke Air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	80/100-21
Bore&Stroke	77*52mm	Tyre Rear	110/100-18
StartingDrive	Kick Start(Electric)	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake

Gas-powered
dirt bike



LQ250-B

BASIC PARAMETER			
Product size	1800*730*1100mm	Max Loading	100kgs
Seat height	850mm	Packing size	1510*390*720mm
Wheel base	1260mm	G.W/N.W	82/72Kgs
Ground clearance	340mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	70/100-17 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	90/100-14 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



LQ250-D

BASIC PARAMETER			
Product size	2130*810*1225mm	Max Loading	150kgs
Seat height	920 mm	Packing size	1740*450*990mm
Wheel base	1450mm	G.W/N.W	135kgs/120kgs
Ground clearance	320mm	Container loads	35pcs/20FT, 85pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	250cc Single-cylinder 4-stroke Air-cooled	Rim Material	Iron or aluminum
Gasoline	#92up	Tyre Front	80/100-21
Bore&Stroke	77*52mm	Tyre Rear	110/100-18
StartingDrive	Kick Start(Electric)	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	100Km/h	Brakes Rear	Hydraulic Disc Brake



LQ250-C

BASIC PARAMETER			
Product size	1800*730*1100mm	Max Loading	100kgs
Seat height	850mm	Packing size	1510*390*720mm
Wheel base	1260mm	G.W/N.W	82/72Kgs
Ground clearance	340mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	70/100-17 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	90/100-14 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-A

BASIC PARAMETER			
Product size	1800*730*1100mm	Max Loading	100kgs
Seat height	850mm	Packing size	1510*390*720mm
Wheel base	1260mm	G.W/N.W	82/72Kgs
Ground clearance	340mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	70/100-17 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	90/100-14 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



LQ125-D

BASIC PARAMETER			
Product size	1800*730*1100mm	Max Loading	100kgs
Seat height	850mm	Packing size	1510*390*720mm
Wheel base	1260mm	G.W/N.W	82/72Kgs
Ground clearance	340mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	125cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	70/100-17 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	90/100-14 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



Gas-powered
dirt bike



LQ110-A

BASIC PARAMETER			
Product size	1500*750*1000mm	Max Loading	80kgs
Seat height	730mm	Packing size	1300*340*700mm
Wheel base	1030mm	G.W/N.W	68/58Kgs
Ground clearance	260mm	Container loads	52pcs/20FT, 177pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	110cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	60/100-14 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	80/100-12 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



LQ110-B

BASIC PARAMETER			
Product size	1800*730*1100mm	Max Loading	100kgs
Seat height	850mm	Packing size	1510*390*720mm
Wheel base	1260mm	G.W/N.W	82/72Kgs
Ground clearance	340mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	110cc Four Stroke, Single Cylinder Air Cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	70/100-17 Air Tire
Bore&Stroke	52.4*49.5mm	Tyre Rear	90/100-14 Air Tire
StartingDrive	Kick Start+Electric Start	Suspension Front	Front Dual Shock absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	1-N-2-3-4(Automatic)	Brakes Front	Hydraulic Disc Brake
Max speed	60Km/h	Brakes Rear	Hydraulic Disc Brake



LQ49-A

BASIC PARAMETER			
Product size	1200*550*750nn	Max Loading	50kgs
Seat height	560 mm	Packing size	1100*275*560mm
Wheel base	860mm	G.W/N.W	26kgs/24kgs
Ground clearance	250mm	Container loads	168pcs/20FT, 396pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	49cc two stroke ,single - cylinder Air cooled	Rim Material	Steel Rim
Gasoline	25:1fuel mixture	Tyre Front	2.50-10 Air Tire
Bore&Stroke	44*33mm	Tyre Rear	2.50-10 Air Tire
StartingDrive	Pull start	Suspension Front	Front Dual Shock Absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	Automatic, Single Forward	Brakes Front	Mechanical Disc Brake
Max speed	35Km/h	Brakes Rear	Mechanical Disc Brake



Gas-powered
dirt bike



LQ49-B

BASIC PARAMETER			
Product size	1200*550*750mm	Max Loading	50kgs
Seat height	560 mm	Packing size	110x275x560mm
Wheel base	860mm	G.W/N.W	26kgs/24kgs
Ground clearance	250mm	Container loads	168pcs/20FT, 396pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	49cc two stroke ,single - cylinder Air cooled	Rim Material	Steel Rim
Gasoline	25:1fuel mixture	Tyre Front	2.50-10 Air Tire
Bore&Stroke	44*33mm	Tyre Rear	2.50-10 Air Tire
StartingDrive	Pull start	Suspension Front	Front Dual Shock Absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	Automatic, Single Forward	Brakes Front	Mechanical Disc Brake
Max speed	35Km/h	Brakes Rear	Mechanical Disc Brake



LQ49-C

BASIC PARAMETER			
Product size	1200*550*750mm	Max Loading	50kgs
Seat height	560 mm	Packing size	1070*290*560mm
Wheel base	860mm	G.W/N.W	25kgs/23kgs
Ground clearance	250mm	Container loads	168pcs/20FT, 396pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	49cc two stroke ,single - cylinder Air cooled	Rim Material	Steel Rim
Gasoline	25:1fuel mixture	Tyre Front	2.50-10 Air Tire
Bore&Stroke	44*33mm	Tyre Rear	2.50-10 Air Tire
StartingDrive	Pull start	Suspension Front	Front Dual Shock Absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	Automatic, Single Forward	Brakes Front	Mechanical Disc Brake
Max speed	35Km/h	Brakes Rear	Mechanical Disc Brake



LQ49-D

BASIC PARAMETER			
Product size	1200*550*750mm	Max Loading	50kgs
Seat height	560 mm	Packing size	1100x275x560mm
Wheel base	860mm	G.W/N.W	28kgs/26kgs
Ground clearance	250mm	Container loads	168pcs/20FT, 396pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Engine	49cc four stroke ,single - cylinder Air cooled	Rim Material	Steel Rim
Gasoline	#92up	Tyre Front	2.50-10 Air Tire
Bore&Stroke	44*33mm	Tyre Rear	2.50-10 Air Tire
StartingDrive	Pull start	Suspension Front	Front Dual Shock Absorber
Drive	Chain Drive	Suspension Rear	Rear Single Spring Shock absorber
Transmission	Automatic, Single Forward	Brakes Front	Mechanical Disc Brake
Max speed	35Km/h	Brakes Rear	Mechanical Disc Brake



Electric dirt bike



LQ-A



BASIC PARAMETER			
Product size	1200*550*750mm	Max Loading	50kgs
Seat height	560 mm	Packing size	1100*275*560mm
Wheel base	860mm	G.W/N.W	39kgs/35kgs
Ground clearance	250mm	Container loads	168pcs/20FT, 396pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor	36V 800W brush magnetic motor	Rim Material	Steel Rim
Battery	12Ah acid-lead battery	Tyre Front	2.50-10 Air Tire
StartingDrive	Electric start	Tyre Rear	2.50-10 Air Tire
Drive	Chain Drive	Suspension Front	Front Dual Shock Absorber
Transmission	Automatic, Single Forward	Suspension Rear	Rear Single Spring Shock absorber
Max speed	35Km/h	Brakes Front	Mechanical Disc Brake
		Brakes Rear	Mechanical Disc Brake

Electric dirt bike



LQ-B

BASIC PARAMETER			
Product size	1550*620*890mm	Max Loading	100kgs
Seat height	730 mm	Packing size	1365*335*640mm
Wheel base	1050mm	G.W/N.W	66kgs/56kgs
Ground clearance	300mm	Container loads	90pcs/20FT, 200pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor	48V 1000W brushless motor	Rim Material	Steel Rim
Battery	20.8 Ah lithium battery	Tyre Front	60/100-14 Air Tire
StartingDrive	Electric start	Tyre Rear	80/100-12 Air Tire
Drive	Chain Drive	Suspension Front	Front Dual Shock absorber
Transmission	Automatic, Single Forward	Suspension Rear	Rear Single Spring Shock absorber
Max speed	60Km/h	Brakes Front	Hydraulic Disc Brake
		Brakes Rear	Hydraulic Disc Brake



LQ-C

BASIC PARAMETER			
Product size	1560*730*950mm	Max Loading	100kgs
Seat height	730 mm	Packing size	1370*370*640mm
Wheel base	1100mm	G.W/N.W	66kgs/56kgs
Ground clearance	300mm	Container loads	90pcs/20FT, 200pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor	48V 3000W brushless motor	Rim Material	Steel Rim
Battery	20.8 Ah lithium battery	Tyre Front	60/100-14 Air Tire
StartingDrive	Electric start	Tyre Rear	80/100-12 Air Tire
Drive	Chain Drive	Suspension Front	Front Dual Shock absorber
Transmission	Automatic, Single Forward	Suspension Rear	Rear Single Spring Shock absorber
Max speed	60Km/h	Brakes Front	Hydraulic Disc Brake
		Brakes Rear	Hydraulic Disc Brake



LQ-D

BASIC PARAMETER			
Product size	1700*730*1100mm	Max Loading	100kgs
Seat height	860 mm	Packing size	1570*380*760mm
Wheel base	1200mm	G.W/N.W	85kgs/70kgs
Ground clearance	380mm	Container loads	70pcs/20FT, 160pcs/40HQ
ENGINE&DRIVETRAIN		BRAKE&TRANSMISSION	
Motor	60V 3000W brushless motor	Rim Material	Steel Rim
Battery	32Ah lithium battery	Tyre Front	70/100-17 Air Tire
StartingDrive	Electric start	Tyre Rear	90/100-14 Air Tire
Drive	Chain Drive	Suspension Front	Front Dual Shock absorber
Transmission	Automatic, Single Forward	Suspension Rear	Rear Single Spring Shock absorber
Max speed	60Km/h	Brakes Front	Hydraulic Disc Brake
		Brakes Rear	Hydraulic Disc Brake